

Waterproof Hi-Fi Column Speaker



Aluminum alloy multi bracket



Frequency-division Circuit



Switch Control

Specifications

Model No.	WS-4120	WS-6130	WS-8140
Rated Power (rms)	20W	30W	40W
Number of Loudspeakers	3.5" Woofer x 4 + 3.25" Tweeter x 1	3.5" Woofer x 6 + 3.25" Tweeter x 1	3.5" Woofer x 8 + 3.25" Tweeter x 1
Power Rating (100V)	20W-10W-5W-2.5W	30W-15W-7.5W-3.75W	40W-20W-10W-5W
Power Rating (70V)	10W-5W-2.5W-1.25W	15W-7.5W-3.75W-1.875W	20W-10W-5W-2.5W
Impedance	500Ω-1KΩ-2KΩ-4KΩ	333Ω-667Ω-1333Ω-2667Ω	250Ω-500Ω-1KΩ-2KΩ
Sensitivity (1W/1M)	92dB	93dB	94dB
MAX. S.P.L.	105dB	108dB	110dB
Frequency Response (-10dB)	130Hz~20KHz	120Hz~20KHz	110Hz~20KHz
Dispersion 1KHz/4KHz	180°/130°	180°/140°	180°/150°
Water Resistant Rating	IP55		
Power Selection	Switch Controller for 4-level 100V/70V high impedance and 6/8Ω low impedance		
Dimension (LWD)	610x124x108 (mm)	813x124x108 (mm)	1016x124x108 (mm)
Material	Housing: aluminum alloy; Grille: aluminum		
Weight	4.2Kgs	5.8Kgs	7.9Kgs
Mounting	Aluminum alloy multi bracket		