

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® TSK302 – 2x1,50 mm²

Halogen Free

Fire Detection Shielded Cable – PH120

Firestop®



A	B	C	D
---	---	---	---

CATEGORY Fire Safety Cable (See news brochure)

APPLICATIONS Fire Detection systems.

- A:** Red **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free. Resistant to direct fire for 120 minutes at max 850°C. Outer cable Ø 7,80 (±0,10) mm.
- B:** Shielding with metallic tape covering 100% + tinned copper drain Wire.
- C:** Core Insulation in **silicon rubber** grade G4, colored one Red and one Black. Twisted together and grouped with PET tape. Diam. Ø 2,80 (±0,10) mm.
- D:** O.F.C. red copper formation 28x0,25 mm. Nom. Cross section 2x1,50 mm².

MARKING **tasker®** TSK302 – 2x1,50 mm² – Fire Detection Shielded Cable EN50200 (PH120) – UNI 9795 – U_o/U 100/100 V – CEI 60332-3-25 - CEI 20-105 - U_o = 400 V – Made in Italy

Cable Properties

Conductor Resistance	13,30 Ω/Km
Max Rated Voltage	100 V
Max Pull Strength	15 kg/150N
Impedance	110 Ω
Min. Bending Radius	10xouterØ
Operative Temperature	-30/+70°C
Temperature Under Fire	850°C/120 min.

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. A / 16.06.17
	X	Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			