





IBZA 8: Compact Full Range Loudspeaker



IBIZA ONE series

MAIN APPLICATIONS

- Background Music in restaurants, airports
- Museums and AV spaces
- Corporative events, exhibitions.
- Hotels, Dance clubs, lounge bars, music pubs
- Distibuted, Fill and Bajo Balcony

MAIN FEATURES

- Compact two-way passive system
- 1 x 8" LF 1 x cone paper tweeter HF
- 8 Ω nominal impedance
- Mounting accessories

DESCRIPTION

The **IBIZA8** is a trapezoidal extremely compact "full range" two-way loudspeaker, which houses a 8" woofer treated with a weather protected membrane and one especial high frequency cone tweeter. It has a highly extended bass performance for such a small volume, with a well-balanced mid and very smooth and natural high section.

This system is designed for professional application where hi-fi quality is required from a compact enclosure. It has been designed for use as stand-alone full range or together with a passive sub-woofer (E.G. SW115).

The box houses multiple internal rigging points for groundsupport, truss and wall mounting, and Speakon NL4 connectors. The cabinet construction has been made in 16mm birch plywood and finished in black semi-matt texture Polyurea weatherized coating. Is resistant to any type of mechanical stress, without vibrating. Housing multiple internal rigging point and is equipped with two Speakon™ NL4 connectors and two recessed carrying handle.

| | |
|--|---|
| Frequency Response | 42 Hz - 20 kHz* |
| Frequency Response: Free Field | 65 Hz - 18 kHz ±4 dB |
| SPL (1m) | 117 dB SPL |
| Maximum Peak SPL | 123 dB SPL |
| Transducers: Low/High Frequency | 1 x 8" LF cone drivers and 1 x cone paper tweeter HF driver |
| Sensitivity (1W/1m) | 97dB |
| Dispersions (HxV) | 110° x 110° |
| Recommended amplifier | PA900/PA4.450/T10-44 |
| Power (AES) | 200 W |
| Power (Peak) | 400 W |
| Rate Impedance | 8 Ω |
| Input Connectors | IN: 1 x NL4 SpeakON® LINK: 1 x NL4 SpeakON® |
| NET Weight | 8,7 kg (19,18 lbs) |
| Dimensions | 254,5 x 254 x 405 mm (HxWxD) (15.95" x 10.02" x 10") |
| Construction | 16mm birch plywood. Finished in black semi-matt texture Polyurea weatherized coating. |
| Protective Grille | Powder coated perforated steel with acoustically transparent reticulated foam |

*Recommended maximum operating frequency range. Response depends on loading conditions and room acoustics.



Pº Ind. Monte Boyal, C/Encinar 282
45950 Casarrubios del Monte (Toledo), SPAIN.
Phone: +34 918 170 110
Fax: +34 918 183 053
www.tecnaire.com
sales@tecnaire.com