



MILAN S.r.l.
Head Office - Export Dept.:
 20090 Cusago (MI) - Italy
 Viale Europa, 74
 Tel. +39 02 90394556 - 4158
 Fax. +39 02 90394551
 www.taskercables.com

**Ufficio Commerciale
 e Centro Distribuzione**
 20090 Cusago (MI) - Italia
 Viale Europa, 72 Strada F12
 Tel. +39 02 90390037 - 59
 Fax +39 02 90390049
 www.tasker.it

NEW Coaxial Cable RG 59 EXTRA - 75 Ω

(for video-frequency)



Code	Cond. number	Nominal section	Cond. Format. mm.	External Core Ø mm.	External Ø mm.	Reel or Spool mt.	Conductor Resistance Ω/Km ± 5%	Impedance Ω ± 3%	Capacity Core/shield pF/mt									
RG 59 Extra	1	1 x 75 Ω	1 x 0,58	3,7	6,1	100 250 500	75	75	67									
		mm ² 0,27 AWG 23	CW	Insulation in PE	Sheath in PVC Black	Attenuation db/100mt <table border="1" style="margin: auto;"> <tr> <td>50 MHz</td> <td>100 MHz</td> <td>200 MHz</td> <td>400 MHz</td> <td>860 MHz</td> </tr> <tr> <td>7,8</td> <td>11,5</td> <td>16,6</td> <td>23,9</td> <td>36,2</td> </tr> </table>					50 MHz	100 MHz	200 MHz	400 MHz	860 MHz	7,8	11,5	16,6
50 MHz	100 MHz	200 MHz	400 MHz	860 MHz														
7,8	11,5	16,6	23,9	36,2														
							Velocity of propagation: 66%		Operative temperature °C -15/+70°									

Cable **tasker®** RG 59 EXTRA

- Single-wired conductor in CW (auburn steel)
- Suggested for crimping BNC
- PE insulation
- Braided shielding in red copper O.F.C. **with covering: 77%.**
- Sheath in PVC Black colour

Coaxial cable with 75 Ω impedance, extra flexible for video frequency, suitable for professional BNC connectors (crimp type) and for the realization of cables and extensions for antenna VHF and UHF signals and for Video devices such as: Home cinema, flat TV, Plasma Screens, LCD, VCR, TC, DVD, SAT receivers, Decoders, and other table or portable devices etc...

MILAN S.r.l. - tasker®
 Technical Dept.